

## Features

- Small Signal Gain 28dB
- Low Gain Flatness
- Input VSWR 2.5
- Output Power 34dBm
- RoHS and REACH Compliant

## Electrical Specifications

Description	Units	Minimum	Typical	Maximum
Freq. Range	GHz	29		31
Small Signal Gain	dB	28		
Gain Flatness	dB		±1.5	±2.0
Noise figure	dB		-	
Output Power @P1dB	dBm	34	35	
Input VSWR	: 1			2.5
Output VSWR	: 1			2.5
OIP3	dBm		-	
Reverse Isolation	dB	-		
Spurious	dBc	-		
Harmonics	dBc			
TTL Control				
TTL Switching Time	us		-	
Supply Current (Vcc=+12 to +15V)	mA		1500	
Operating Temp.	°C	-40		+50

## Special Requirements

## Note

- Electronic Specification Note : Values at 25deg , sea level. Test indicators will deteriorate at high and low temperature ;
- ESD sensitive material , Transport material in approved ESD bags. Handle only in approved ESD workstation;
- Providing effective cooling measures and electrostatic protection;
- If the product is damaged due to over-drive, no-load, over-temperature, over-current and static electricity in use. Customer needs to pay for the cost of maintenance.


## Mechanical Specifications

Dimension L*W*H	35*55*12 mm
Input Connector	2.92mm-Female
Output Connector	2.92mm-Female
Weight	TBD g
Finishing	Nickel Plated
Environment	X

## Compliance Certifications

RoHS Compliant	✓
REACH Compliant	✓

## CAD Drawing



Dimensions are in mm [Inches]  
Tolerances : Outline drawing:  $\pm 0.2$  [0.008]  
Hole:  $\pm 0.2$  [0.008]