

## Features

- Design : Wilkinson
- Stainless Steel Connectors
- Low Insertion Loss 1.2dB
- RoHS and REACH Compliant
- High Isolation 16dB

## Electrical Specifications

Description	Units	Minimum	Typical	Maximum
Freq. Range	GHz	1		10
Nominal Splitter Loss	dB		3.0	
Insertion Loss	dB			1.2
Input VSWR				1.4
Output VSWR				1.3
Amplitude Balance	dB			0.4
Phase Balance	deg			6
Isolation	dB	16		
Forward Power	W			20
Reverse Power	W			1
Peak Power	KW			0.5
Impedance	Ohms		50	
Operating Temp.	°C	-40		+70

## Special Requirements

## Note

- Electronic Specification Note : Values at 25deg , sea level. Test indicators will deteriorate at high and low temperature ;
- All output ports /power combiner in-amplitude (0dB difference) ;
- All output ports /power combiner in-phase (0° difference) ;


**Mechanical Specifications**

Dimension L*W*H	24*80*10 mm
Input Connector	SMA-Female Stainless Steel
Output Connectors	SMA-Female Stainless Steel
Weight	TBD g
Finishing	Paint Black
Environment	Nominal

**Compliance Certifications**

RoHS Compliant	✓
REACH Compliant	✓

**CAD Drawing**



Dimensions are in mm [Inches]  
 Tolerances : Outline drawing: ±0.2 [0.008]  
 Hole: ±0.2 [0.008]