

Features

- Design : Wilkinson
- Ni Plating Connectors
- Low Insertion Loss 3.3dB
- RoHS and REACH Compliant
- High Isolation 20dB

Electrical Specifications

Description	Units	Minimum	Typical	Maximum
Freq. Range	GHz	5		6
Nominal Splitter Loss	dB		3.0	
Insertion Loss	dB			3.3
Input VSWR				1.2
Output VSWR				1.2
Amplitude Balance	dB			0.3
Phase Balance	deg			3
Isolation	dB	20		
Forward Power	W			20
Reverse Power	W			
Peak Power	KW			
Impedance	Ohms		50	
Operating Temp.	°C	-40		+85

Special Requirements

Note

- Electronic Specification Note : Values at 25deg , sea level. Test indicators will deteriorate at high and low temperature ;
- All output ports /power combiner in-amplitude (0dB difference) ;
- All output ports /power combiner in-phase (0° difference) ;


Mechanical Specifications

Dimension L*W*H	53.6*33*19 mm
Input Connector	N-Male Ni Plating
Output Connectors	N-Female Ni Plating
Weight	TBD g
Finishing	Paint Black
Environment	IP67

Compliance Certifications

RoHS Compliant	✓
REACH Compliant	✓

CAD Drawing



Dimensions are in mm [Inches]
 Tolerances : Outline drawing: ±0.2 [0.008]
 Hole: ±0.2 [0.008]