

Features

- Design : Wilkinson
- Ni Plating Connectors
- Low Insertion Loss 0.6dB
- RoHS and REACH Compliant
- High Isolation 20dB

Electrical Specifications

Description	Units	Minimum	Typical	Maximum
Freq. Range	GHz	1		2
Nominal Splitter Loss	dB		6.0	
Insertion Loss	dB			0.6
Input VSWR				1.3
Output VSWR				1.25
Amplitude Balance	dB			0.3
Phase Balance	deg			4
Isolation	dB	20		
Forward Power	W			30
Reverse Power	W			1
Peak Power	KW			0.5
Impedance	Ohms		50	
Operating Temp.	°C	-45		+85

Special Requirements

Note

- Electronic Specification Note : Values at 25deg , sea level. Test indicators will deteriorate at high and low temperature ;
- All output ports /power combiner in-amplitude (0dB difference) ;
- All output ports /power combiner in-phase (0° difference) ;


Mechanical Specifications

Dimension L*W*H	97*49*20 mm
Input Connector	N-Female Ni Plating
Output Connectors	N-Female Ni Plating
Weight	270 g
Finishing	Paint Black
Environment	Nominal

Compliance Certifications


RoHS Compliant	✓
REACH Compliant	✓

CAD Drawing




Dimensions are in mm [Inches]
 Tolerances : Outline drawing: ±0.2 [0.008]
 Hole: ±0.2 [0.008]


Input Port VSWR




Output Port VSWR




Output Port Insertion Loss



Output Port Isolation



Amplitude Balance



Phase Balance

