

## Features

- Design : Wilkinson
- Stainless Steel Connectors
- Low Insertion Loss 1.5dB
- RoHS and REACH Compliant
- High Isolation 20dB

## Electrical Specifications

Description	Units	Minimum	Typical	Maximum
Freq. Range	GHz	1.4		5.3
Nominal Splitter Loss	dB		6.0	
Insertion Loss	dB			1.5
Input VSWR				1.5
Output VSWR				1.5
Amplitude Balance	dB			1
Phase Balance	deg			10
Isolation	dB	20		
Forward Power	W			10
Reverse Power	W			1
Peak Power	KW			1
Impedance	Ohms		50	
Operating Temp.	°C	-40		+70

## Special Requirements

## Note

- Electronic Specification Note : Values at 25deg , sea level. Test indicators will deteriorate at high and low temperature ;
- All output ports /power combiner in-amplitude (0dB difference) ;
- All output ports /power combiner in-phase (0° difference) ;


### Mechanical Specifications

Dimension L*W*H	59*52*10 mm
Input Connector	SMA-Female Stainless Steel
Output Connectors	SMA-Female Stainless Steel
Weight	75 g
Finishing	Paint Black
Environment	Nominal

### Compliance Certifications


RoHS Compliant	✓
REACH Compliant	✓

### CAD Drawing




Dimensions are in mm [Inches]  
 Tolerances : Outline drawing: ±0.2 [0.008]  
 Hole: ±0.2 [0.008]


## Input Port VSWR




## Output Port VSWR




## Output Port Insertion Loss



## Output Port Isolation



## Amplitude Balance



## Phase Balance

