

## Features

- Design : Wilkinson
- Stainless Steel Connectors
- Low Insertion Loss 3.0dB
- RoHS and REACH Compliant
- High Isolation 15dB

## Electrical Specifications

Description	Units	Minimum	Typical	Maximum
Freq. Range	GHz	3		40
Nominal Splitter Loss	dB		6.0	
Insertion Loss	dB			3.0
Input VSWR				2.0
Output VSWR				1.6
Amplitude Balance	dB			1.0
Phase Balance	deg			20
Isolation	dB	15		
Forward Power	W			20
Reverse Power	W			-
Peak Power	KW			0.2
Impedance	Ohms		50	
Operating Temp.	°C	-45		+85

## Special Requirements

## Note

- Electronic Specification Note : Values at 25deg , sea level. Test indicators will deteriorate at high and low temperature ;
- All output ports /power combiner in-amplitude (0dB difference) ;
- All output ports /power combiner in-phase (0° difference) ;


## Mechanical Specifications

Dimension L*W*H	46*47*12.7 mm
Input Connector	2.4mm-Female Stainless Steel
Output Connectors	2.4mm-Female Stainless Steel
Weight	TBD g
Finishing	Paint Black
Environment	Nominal

## Compliance Certifications

RoHS Compliant	✓
REACH Compliant	✓

## CAD Drawing



Dimensions are in mm [Inches]  
 Tolerances : Outline drawing: ±0.2 [0.008]  
 Hole: ±0.2 [0.008]