

## Features

- Design : SP13T Absorptive
- Ultra Wide Band
- Low Insertion Loss 3.8 dB
- Fast Switching Speed
- RoHS and REACH Compliant

## Electrical Specifications

Description	Units	Minimum	Typical	Maximum
Freq. Range	GHz	3		6
Input Power	W		1	
Insertion Loss	dB		3.5	3.8
VSWR	:1			1.7
Isolation	dB	60		
Switching speed	nsec			100
Rise / Fall time	nsec			-
DC Biasing (+5V)	mA		650	
DC Biasing (-5V)	mA		100	
Control Interface			PIN	
Control Type			TTL	
Impedance	Ohms		50	
Operating Temp.	°C	-45		+85

## Special Requirements

## Note

- Electronic Specification Note : Values at 25deg , sea level. Test indicators will deteriorate at high and low temperature ;
- Switching speed is 50% TTL to 90% RF ( T- ON ) and 50% TTL to 10% RF ( T- OFF) ;
- Rise / Fall time : 10% RF to 90% RF and 90% RF to 10% RF ;

## Mechanical Specifications

Dimension L*W*H	165.1*40*10.2 mm
Input Connector	SMA-Female Stainless Steel
Output Connectors	SMA-Female Stainless Steel
Weight	310 g
Finishing	Nickel Plated
Environment	Nominal
RoHS / REACH Compliant	✓

## Truth Table

Control Input TTL				Signal Path State
E4	E3	E2	E1	
0	0	0	0	J0-J1
0	0	0	1	J0-J2
0	0	1	0	J0-J3
0	0	1	1	J0-J4
0	1	0	0	J0-J5
0	1	0	1	J0-J6
0	1	1	0	J0-J7
0	1	1	1	J0-J8
1	0	0	0	J0-J9
1	0	0	1	J0-J10
1	0	1	0	J0-J11
1	0	1	1	J0-J12
1	1	0	0	J0-J13

- TTL Control Voltage : High ( 1 ) : 2.8 to 5V
- TTL Control Voltage : Low ( 0 ) : 0 to 0.8V
- Low Power cold Switching

## CAD Drawing

