

## Features

- Design : SPST Absorptive
- Ultra Wide Band
- Low Insertion Loss 3 dB
- Fast Switching Speed
- RoHS and REACH Compliant

## Electrical Specifications

Description	Units	Minimum	Typical	Maximum
Freq. Range	GHz	2		18
Input Power	W		1	
Insertion Loss	dB			3
VSWR	:1			2
Isolation	dB	60		
Switching speed	nsec			100
Rise / Fall time	nsec			-
DC Biasing (+5V)	mA		50	
DC Biasing (-5V)	mA		50	
Control Interface			PIN	
Control Type			TTL	
Impedance	Ohms		50	
Operating Temp.	°C	-45		+85

## Special Requirements

## Note

- Electronic Specification Note : Values at 25deg , sea level. Test indicators will deteriorate at high and low temperature ;
- Switching speed is 50% TTL to 90% RF ( T- ON ) and 50% TTL to 10% RF ( T- OFF) ;
- Rise / Fall time : 10% RF to 90% RF and 90% RF to 10% RF ;

**Mechanical Specifications**


Dimension L*W*H	24*20*10.20 mm
Input Connector	SMA-Female Stainless Steel
Output Connectors	SMA-Female Stainless Steel
Weight	15 g
Finishing	Gold Plated
Environment	Nominal
RoHS / REACH Compliant	✓

**Truth Table**

Control Input TTL	Signal Path State
E1 or TTL	
0	ON
1	OFF


- TTL Control Voltage : High ( 1 ) : 2.8 to 5V
- TTL Control Voltage : Low ( 0 ) : 0 to 0.8V
- Low Power cold Switching

**CAD Drawing**




Dimensions are in mm [Inches]  
Tolerances : Outline drawing: ±0.2 [0.008]  
Hole: ±0.2 [0.008]


## J0 - J1




## J1 Isolation




## J0 - J2



## J2 Isolation



## Turn On Switching Speed



## Turn Off Switching Speed

