

Features

- External Reference
- Output Power : 13dBm
- Output Freq. : 9.9 GHz
- Harmonics : -20 dBc
- RoHS and REACH Compliant

Electrical Specifications

Description	Units	Minimum	Typical	Maximum
Output Frequency	GHz		9.9	
Output Power	dBm		13±1	
Phase Noise@10Hz	dBc/Hz			
Phase Noise@100Hz	dBc/Hz			-75
Phase Noise@1KHz	dBc/Hz			-100
Phase Noise@10KHz	dBc/Hz			-110
Phase Noise@100KHz	dBc/Hz			-116
Phase Noise@1MHz	dBc/Hz			-128
Reference Frequency	MHz		100	
Reference Input Power	dBm		0 ±3	
2nd Harmonics	dBc		-20	
Spurious	dBc		-60	
Supply Voltage	V	+	+ 12	+
Current	mA		250	
Operating Temp.	°C	-5		+65
Lock Detect	TTL High (3.3V - 5V) in Lock ; TTL Low (0V -0.7V) Unlock			

Note

- Electronic Specification Note : Values at 25deg , sea level. Test indicators will deteriorate at high and low temperature ;
- External Reference & Dual Loop Models Frequency Stability : Same as External Reference.
- External Ref. Phase noise deteriorate : =20 log (Output Freq / Ref. Freq) +3


Mechanical Specifications

Dimension L*W*H	47.8*50.8*15.7 mm
Ref. Connector	SMA-Female Stainless Steel
Output Connectors	SMA-Female Stainless Steel
Weight	85 g
Finishing	Silver Plated
Environment	Nominal

Compliance Certifications

RoHS Compliant	✓
REACH Compliant	✓

CAD Drawing



Dimensions are in mm [Inches]
Tolerances : Outline drawing: ±0.2 [0.008]
Hole: ±0.2 [0.008]