

Features

- Internal Reference
- Output Power : 13dBm
- Output Freq. : 15 GHz
- Harmonics : -20 dBc
- RoHS and REACH Compliant

Electrical Specifications

Description	Units	Minimum	Typical	Maximum
Output Frequency	GHz		15	
Output Power	dBm		13	
Phase Noise@10Hz	dBc/Hz			
Phase Noise@100Hz	dBc/Hz			-78
Phase Noise@1KHz	dBc/Hz			-108
Phase Noise@10KHz	dBc/Hz			-112
Phase Noise@100KHz	dBc/Hz			-112
Phase Noise@1MHz	dBc/Hz			-124
Reference Frequency	MHz		-	
Reference Input Power	dBm		-	
2nd Harmonics	dBc		-20	
Spurious	dBc		-70	
Supply Voltage	V		+12	+
Current	mA		600	
Operating Temp.	°C	-40		+70
Lock Detect	TTL High (3.3V - 5V) in Lock ; TTL Low (0V -0.7V) Unlock			

Note

- Electronic Specification Note : Values at 25deg , sea level. Test indicators will deteriorate at high and low temperature ;
- External Reference & Dual Loop Models Frequency Stability : Same as External Reference.
- External Ref. Phase noise deteriorate : =20 log (Output Freq / Ref. Freq) +3

Mechanical Specifications

Dimension L*W*H	mm
Ref. Connector	- Stainless Steel
Output Connectors	SMA-Female Stainless Steel
Weight	TBD g
Finishing	Nickel Plated
Environment	Nominal

Compliance Certifications

RoHS Compliant	✓
REACH Compliant	✓

CAD Drawing

Dimensions are in mm [Inches]
Tolerances : Outline drawing: ± 0.2 [0.008]
Hole: ± 0.2 [0.008]